

4.5 Probe Holder Accessories

Probe Holder Accessories



Sample Water Low Flow Switch, suitable for fitting to inlet connection on by-pass probe holder assembly, (8 x 5). Arranged to pause controller. This unit is fitted with opposing magnets that act like a spring so it can be mounted in any position. Supplied complete with fittings. Normally Open or Normally Closed contacts available.

Part No.

Low Flow Switch, SW15 connections mounting in any position

PA03022425

P20-C

Low Flow Switch, SW15 connections only without magnets - vertical mounting only

P20-NM

Low Flow Switch, paddle type, pipe size 25 -150mm

F-H-25B



Flexible submersion pipe assembly to be used with DYNAPROBE or the MKII Gland Assembly below.

PA02032256



Adaptor PVC tube fitting, from J-Box to 23x16 hose

A27021362

Cap Nut

356562



J-Box assembly with 2 glands and terminal strip for joining extension cable, pulse cable, probe cables, etc.

PA03021783

COMPONENTS FOR INDUSTRIAL SUBMERSIBLE ELECTRODE HOLDERS



1-1/2" full bore valve - Stainless Steel

A09591853



1-1/2" nipple BSPT Hex SS

A07541866



1/2" BSP M/F Ball Valve (nickle plated brass)

BR-B/V-TEE-MXF-15

